



Flat Face Union with PTFE Gasket

DN	A	B	C	Kgs
1/8"	30.5	8.75	13	0.055
1/4"	34	10.25	13.5	0.083
3/8"	37	10.75	15.5	0.105
1/2"	40	12	16	0.116
3/4"	43	13	17	0.198
1"	50.5	15.25	20	0.265
1 1/4"	54.5	16.25	22	0.406
1 1/2"	58	17	24	0.462
2"	65.5	19.25	27	0.684
2 1/2"	75	22.75	29.5	1.470
3"	83.5	26.25	31	1.880
4"	110.5	38.25	34	3.160

- Made from CF8M (316) Stainless Steel material and conform to **ISO 4144** standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.

NOTE 2 Temperatures indicated are those of internal fluid.

NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.