



Hexagon Head Plug

DN	A	B	C	Kgs
1/8"	16.5	10.5	6	0.009
1/4"	19	13	6	0.015
3/8"	19	13	6	0.022
1/2"	23	16	7	0.038
3/4"	25.5	17.5	8	0.056
1"	28.5	20	8.5	0.083
1 1/4"	30	21	9	0.125
1 1/2"	30.5	21	9.5	0.165
2"	35	26	9	0.259
2 1/2"	40	30	10	0.471
3"	44	33	11	0.597
4"	48.5	36	12.5	1.069

- Made from CF8M (316) Stainless Steel material and conform to **ISO 4144** standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.

NOTE 2 Temperatures indicated are those of internal fluid.

NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.