



Hexagon Nipple

DN	A	B	C	Kgs
1/8"	30	12	6	0.016
1/4"	32	13	6	0.021
3/8"	36.5	15	6.5	0.035
1/2"	43	16.5	10	0.050
3/4"	45	18.5	8	0.070
1"	48	18.5	11	0.119
1 1/4"	53	20.5	12	0.180
1 1/2"	55.5	22.5	10.5	0.217
2"	64	25.5	13	0.328
2 1/2"	76	31	14	0.661
3"	80	33	14	0.855
4"	86	36	14	1.327

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

- NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.
- NOTE 2 Temperatures indicated are those of internal fluid.
- NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.