



Hexagon Reducing Bush

DN	A	B	Kgs
1/4" x 1/8"	12	6.5	0.013
3/8" x 1/4"	14	6.5	0.021
1/2" x 1/4"	16.5	7.5	0.035
1/2" x 3/8"	17	7	0.031
3/4" x 1/4"	18	8	0.065 NEW
3/4" x 3/8"	18	8	0.055 NEW
3/4" x 1/2"	18	8	0.048
1" x 1/2"	19	8	0.081
1" x 3/4"	19	8	0.067
1 1/4" x 1/2"	20.5	9	0.143
1 1/4" x 3/4"	20.5	9	0.141
1 1/4" x 1"	20.5	9	0.114
1 1/2" x 1/2"	22	9	0.200 NEW
1 1/2" x 3/4"	22	9	0.197
1 1/2" x 1"	22	9	0.176
1 1/2" x 1 1/4"	22	9	0.121
2" x 1"	26	9	0.328
2" x 1 1/4"	26	9	0.269
2" x 1 1/2"	26	9	0.228
2 1/2" x 2"	27	8	0.445
3" x 2"	33	11	0.795
3" x 2 1/2"	33	11	0.589
4" x 2"	36	12	1.492
4" x 3"	36	12	1.203

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.

NOTE 2 Temperatures indicated are those of internal fluid.

NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.