



Hexagon Nipple

DN	A	B	C	Kgs
1/8"	30.3	12	6.3	0.016
1/4"	32	13.4	5.2	0.021
3/8"	36.7	14.8	7.1	0.035
1/2"	41.7	16.4	8.8	0.050
3/4"	45	18.5	8	0.070
1"	48.1	18.6	10.9	0.119
1 1/4"	53.4	20.6	12.2	0.180
1 1/2"	55.5	21.5	12.5	0.217
2"	64.2	25.6	13	0.328
2 1/2"	76	30.8	14.4	0.661
3"	79.7	33.3	13.1	0.855
4"	85.7	36	13.7	1.327

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.

NOTE 2 Temperatures indicated are those of internal fluid.

NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.