



Reducing Hexagon Nipple

DN	A	B	C	D	Kgs
1/4" x 1/8"	30	13.3	11	5.7	0.017
3/8" x 1/4"	35	14.7	13	7.3	0.035
1/2" x 1/4"	38	17	13.9	7.1	0.045
1/2" x 3/8"	39.8	17	14.5	8.3	0.047
3/4" x 1/2"	43.5	18	16.8	8.7	0.074
1" x 1/2"	47	18.9	17	11.1	0.106
1" x 3/4"	48	18.7	18	11.3	0.105
1 1/4" x 1/2"	50	21.2	17.2	11.6	0.159
1 1/4" x 3/4"	51	21.2	18	11.8	0.153
1 1/4" x 1"	52	21.5	19.5	11	0.174
1 1/2" x 3/4"	52.5	22.2	18	12.3	0.220
1 1/2" x 1"	53.2	22.2	19	12	0.222
1 1/2" x 1 1/4"	55	22	21	12	0.224
2" x 1"	57.7	26	19.3	12.4	0.323
2" x 1 1/4"	60.4	25.7	21.4	13.3	0.334
2" x 1 1/2"	60.4	26	22.3	12.1	0.336
2 1/2" x 2"	70.7	31	26	13.7	0.606
3" x 2"	72	33	26	13	0.870
3" x 2 1/2"	77.6	33	31	13.6	0.841
4" x 2"	75.7	36	26	13.7	1.005
4" x 3"	82.7	36	32	14.7	1.180

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.

NOTE 2 Temperatures indicated are those of internal fluid.

NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.