



## Reducing Tee

DN	A	B	C	D	Kgs
3/8" x 1/4"	22	20	20.3	17.6	0.047
1/2" x 1/4"	24	24	27	17.6	0.085
1/2" x 3/8"	25	26	27	20.3	0.086
3/4" x 1/2"	30	29	32	27	0.130
1" x 3/4"	36	34	40.3	32	0.224
1 1/4" x 1"	42	40	48.3	40.3	0.340
1 1/2" x 1 1/4"	48	45	55	47.8	0.442
2" x 1 1/2"	55	52	67.3	55	0.645

- Made from CF8M (316) Stainless Steel material and conform to **ISO 4144** standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

- NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.
- NOTE 2 Temperatures indicated are those of internal fluid.
- NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2008 quality system.