



Hexagon Backnut

DN	A	B	Kgs
1/8"	6	18	0.010
1/4"	6.14	20.96	0.011
3/8"	7.16	26	0.021
1/2"	8	30.99	0.030
3/4"	9.2	35	0.036
1"	10	44.94	0.065
1 1/4"	11.2	54	0.103
1 1/2"	11.88	58.85	0.112
2"	13.2	74	0.203
2 1/2"	15.96	93.5	0.401
3"	19.1	106.2	0.500
4"	23.22	133.9	0.924

- Made from CF8M (316) Stainless Steel material and conform to **ISO 4144** standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

- NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.
- NOTE 2 Temperatures indicated are those of internal fluid.
- NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2015 quality system.