



Hexagon Reducing Bush

DN	A	B	C	D	E	Kgs
1/4" x 1/8"	8.4	15	12	12.5	19	0.013
3/8" x 1/8"	11	19	13	14	20.3	0.023
3/8" x 1/4"	11	19	10	14	20.3	0.021
1/2" x 1/8"	15	22.5	17	17	23.7	0.037
1/2" x 1/4"	15	22.5	15	17	23.7	0.035
1/2" x 3/8"	15	22.5	14	17	23.7	0.031
3/4" x 1/4"	20.5	29	16.4	18	26	0.066
3/4" x 3/8"	20.5	29	16.3	18	26	0.059
3/4" x 1/2"	20.5	29	15.8	18	26	0.048
1" x 1/4"	26	25.5	18.5	19	27	0.101
1" x 3/8"	26	35.5	18	19	27	0.095
1" x 1/2"	26	35.5	17.4	19	27	0.081
1" x 3/4"	26	35.5	13.6	19	27	0.067
1 1/4" x 1/2"	34.5	43.6	20.2	20.5	30	0.143
1 1/4" x 3/4"	34.5	43.6	18.2	20.5	30	0.141
1 1/4" x 1"	34.5	43.6	16	20.5	30	0.121
1 1/2" x 1/2"	40	51	22	22	31	0.206
1 1/2" x 3/4"	40	51	20	22	31	0.197
1 1/2" x 1"	40	51	17	22	31	0.185
1 1/2" x 1 1/4"	40	51	15.5	22	31	0.129
2" x 1/2"	51	62.4	26	26	35	0.318
2" x 3/4"	51	62.4	23	26	35	0.325
2" x 1"	51	62.4	21	26	35	0.328
2" x 1 1/4"	51	62.4	20	26	35	0.274
2" x 1 1/2"	51	62.4	17.8	26	35	0.228
2 1/2" x 1 1/2"	64.5	77.8	24	30	40	0.572
2 1/2" x 2"	65	77.8	22.5	30	39.5	0.443
3" x 1"	77.2	91.2	30	33	44	0.875
3" x 1 1/4"	77.4	91.2	37.5	33	44	0.731
3" x 1 1/2"	77.2	91.2	26.6	33	44	0.871
3" x 2"	77.2	91.2	27.3	33	44	0.795
3" x 2 1/2"	77.2	91.2	20	33	44	0.589
4" x 2"	101.3	116.6	27	36	48	1.488
4" x 3"	101.3	116.6	23.3	36	48	1.203

- Made from CF8M (316) Stainless Steel material and conform to **ISO 4144** standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Pressure temperature ratings. See table below.

Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.

NOTE 2 Temperatures indicated are those of internal fluid.

NOTE 3 Piping loads, stresses and moments are not taken into account.

- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2015 quality system.