



Water Hammer Arrestor

Features

- ART 1335 BSP. ART 1335 NPT
- Lead free
- Precharged, permanent sealed air chamber to absorb the shock
- Approved for installation with no access panel required
- May be installed in new or existing plumbing systems with a standard pipe tee
- Air pre-load is 60psi (4.2 Bar)
- Factory air charged and permanently sealed
- Design standard PDI WH-201

Pipe Sizing

Suffix	Description
A	Conn, Size 1/2" (15), Height 5.945" (151)
B	Conn, Size 3/4" (20), Height 7.264" (184.5)
C	Conn, Size 1" (25), Height 8.799" (223.5)
D	Conn, Size 1" (25), Height 9.941" (252.5)
E	Conn, Size 1" (25), Height 12.697" (322.5)
F	Conn, Size 1" (25), Height 11.161" (283.5)

Technical Data and Dimensions

	A	B	C	D	E	F
Fixture Unit	1-11	12-32	33-60	61-113	114-154	155-330
A	1.125" (28.58)	1.125" (28.58)	1.625" (41.28)	2.125" (53.98)	2.125" (53.98)	2.625" (66.68)
B	5.945" (151)	7.264" (184.5)	8.799" (223.5)	9.941" (252.5)	12.697" (322.5)	11.161" (283.5)
Kgs	0.17	0.22	0.46	0.75	0.92	1.12

No.	Part Name	Materials
1	Body	Copper
2	Piston	Polypropylene
3	O-Rings	EPDM
4	Adaptor	Lead Free Brass

Technical Data

Max Pressure	350psig
Working Pressure	150psi (10.6 Bar)
Working Temperature	0.5°C to 82°C

Dimensions in mm

This data sheet is designed as a guide and should not be regarded as wholly accurate in every detail. We reserve the right to amend the specification of any product without notice.