



HHP

Hexagon Head Plug




Features

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to BSP Taper (ISO 7/1) or NPT (ANSI B1.20.1).
- Material certificates available on request.
- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2015 quality system.



DN	A	B	C	Kgs
1/8"	16.7	10.4	6.3	0.009
1/4"	19.8	13.5	6.3	0.015
3/8"	19.8	13.5	6.3	0.022
1/2"	23.0	16.0	7.0	0.038
3/4"	26.0	17.5	8.5	0.056
1"	29.0	21.0	8.0	0.083
1 1/4"	30.7	21.7	9.0	0.125
1 1/2"	31.0	22.0	9.0	0.165
2"	35.0	26.0	9.0	0.259
2 1/2"	39.6	29.6	10.0	0.471
3"	44.0	33.0	11.0	0.597
4"	48.6	36.6	12.0	1.069



Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

- NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.
- NOTE 2 Temperatures indicated are those of internal fluid.
- NOTE 3 Piping loads, stresses and moments are not taken into account.